CFAIR

ENGINE DRIVEN COMPRESSOR

50-1800CFM 7-30bar / 101.5psi-435psi

ENGINE DRIVEN AIR COMPRESSORS

PROFESSIONAL MANUFACTURER

HANGZHOU CAIFULL PRECISION MACHINERY CO.,LTD
NO.138 BAIJIAYUAN ROAD, XIHU DISTRICT,
HANGZHOU CITY, ZHEJIANG PROVINCE, CHINA.
TEL: 0086-571-85128760 FAX: 0086-571-85128761
Email: info@caifuair.com
Website: www.caifuair.com
WhatsApp:+86-15224036711

BOX SERIES | PORTABLE SERIES | AFTER COOLER SERIES | HIGH PRESSURE SERIES | OIL-FREE SERIES

ENGINE-DRIVEN COMPRESSOR MANUFACTURER

20000+
AIR COMPRESSOR SOLUTIONS

35+
INTERNATIONAL MARKET

45+
TECHNOLOGY HISTORY

CFAIR ENGINE DRIVEN
SCREW AIR COMPRESSORS

PROFESSIONAL MANUFACTURER

CFAIR offers a range of engine driven screw air compressors including Box Type, Portable Type, After Cooler Series, High Pressure Series, and Oil Free models. Equipped with leading global manufacturing equipment, CFAIR ensures rigorous control from precision machining of screw heads, assembly, and system performance testing to comprehensive solution design and exterior finishing by expert teams. CFAIR compressors range in power from 50 CFM to 1800 CFM and operate at pressures from 7 bar to 30 bar.



HIGH-QUALITY SOLUTIONS

CFAIR's team comprises industry experts and seasoned professionals with over 45 years of technical expertise in the design and manufacturing of screw air compressors. With a research and development experience of over 20,000 diesel screw air compressors, they lead and drive the advancement of screw air compressor technology.

CFAIR PRODUCTION PROCESS AND TECHNOLOGY

Our professional production line starts with the production of screw heads, where our team of experts and advanced machines use cutting-edge equipment to ensure excellence and durability. Subsequently, sheet metal production involves processes such as laser cutting, bending, welding, pickling, phosphating, forming and anti-corrosion coating.

Our assembly workshop is equipped with professional tools and skilled personnel to ensure that our production capabilities meet industry standards. Each machine is then rigorously tested and inspected by experts in our quality inspection and testing workshop to ensure that it meets our high quality standards.



QUALITY CERTIFICATE AUTHENTICATION

Quality Management System (QMS) International Standard 9001-2015.

International Standard For Occupational Health And Safety Management Systems 4501-2018.

International Standard For Environmental Management Systems 14001-2015.

CE European Union Standard Certification



MODEL SELECTION

COMPREHENSIVE SOLUTION BOX TYPE SERIES

Box Type

BOX TYPE SCREW AIR COMPRESSOR

A box-type air compressor is a compact and enclosed unit designed for efficient and portable operation in various industrial and construction settings.

CFAIR BOX TYPE AIR COMPRESSOR ADVANTAGES

Whether you need to move on site or prefer a closed solution, professional air compressor manufacturer CFAIR offers a range of options suitable for various applications.

CFAIR BOX TYPE screw air compressors have the advantages of compact appearance, quietness, stability, high performance and longer life.

Its air filter, engine, head, battery, control system, etc. have considerable advantages in all aspects.

BOX TYPE AIR COMPRESSOR



DETAILED DISPLAY

1.DIESEL ENGINES

- CFAIR's main engine brands include Cummins, ISUZU and a small amount of FAW
- Adopting four-stroke four- to six-cylinderengines of various brands, with stableperformance

2.TWO-STAGE AIR FILTERPREFER

- The double-layer nano-scale air filter for diesel air compressors enhances filtration efficiency, extends engine life, improves fuel efficiency, reduces maintenance costs, ensures consistent performance, and offers environmental benefits by capturing finer particles, leading to cleaner air intake and optimal engine operation.

3.VARTA BATTERIES

- VARTA batteries offer superior performance, long lifespan, reliable power, advanced technology, minimal maintenance, and high safety standards, making them ideal for a wide range of applications.

4.STAINLESS OUTLET VALVE

- Stainless steel outlets for diesel air compressors offer durability, corrosion resistance, reliability, longevity, and maintain air purity.

5.EMERGENCY STOP BUTTON

- An emergency stop button for a diesel air compressor enhances safety, allows immediate shutdown in emergencies, prevents damage, reduces risks, and ensures operator protection and equipment reliability.

6.USER FRIENDLY CONTROL PANEL

- CFAIR Diesel Air Compressor Manufacturers design intuitive user-friendly interface, enhanced monitoring, accuracy, improved safety and efficiency to ensure compressor reliability.

BOX TYPE SERIES
AIR COMPRESSOR

Box Type

120 CFM
7BAR

SEPECIFICATION	CF120B-7
Free Air Delivery	3.4m3/min(120cfm)
Working Pressure	7bar(101.5psi)
Model	ISUZU JE493YB
L × W × H	1880 × 915 × 1230 mm
Weight	830kg

190 CFM
7BAR

SEPECIFICATION	CF190B-7
Free Air Delivery	5.4m3/min(190cfm)
Working Pressure	7bar(101.5psi)
Model	ISUZU JE493ZYA
L × W × H	2100 x 980 x 1100 mm
Weight	930kg

275 CFM
7BAR

SEPECIFICATION	CF275B-7
Free Air Delivery	7.8m3/min(275cfm)
Working Pressure	7bar(101.5psi)
Model	ISUZU JE493ZLYA
L × W × H	2280 x 1224 x 1260 mm
Weight	1100kg

400 CFM
7BAR

SEPECIFICATION	CF400B-7
Free Air Delivery	11.3m3/min(400cfm)
Working Pressure	7bar(101.5psi)
Model	CUMMINS 4BTA3.9-C125
L × W × H	2657 x 1355 x 1466 mm
Weight	1850kg

390 CFM
10.5BAR

SEPECIFICATION	CF390B-10.5
Free Air Delivery	11m3/min(390cfm)
Working Pressure	10.5bar(152.25psi)
Model	CUMMINS 6BT5.9-C150
L × W × H	2970 x 1350 x 1465 mm
Weight	1920kg

830 CFM
10.5BAR

SEPECIFICATION	CF830B-10.5
Free Air Delivery	23.4m3/min(830cfm)
Working Pressure	10.5bar(152.25psi)
Model	CUMMINS 6LTAA8.9-C360
L × W × H	3600 x 1950 x 1900 mm
Weight	4200kg

MODEL	FREE AIR DELIVERY	PRESSURE	ENGINE	DIMENSIONS(MM)	WEIGHT(KG)	AIR OUTLETS
CF100B-7	100CFM / 2.8M³/MIN	7BAR / 101.5PSI	ISUZU JE493YB	1880*915*1230	820	2 X 3/4"
CF120B-7	120CFM / 3.4M³/MIN	7BAR / 101.5PSI	ISUZU JE493YB	1880*915*1230	830	2 X 3/4"
CF130B-7	130CFM / 3.7M³/MIN	7BAR / 101.5PSI	ISUZU JE493YB	1880*915*1230	830	2 X 3/4"
CF185B-7	185CFM / 5.2M³/MIN	7BAR / 101.5PSI	FAW 4DW91-56G2	2100*980*1100	930	3 X 3/4"
CF190B-7	190CFM / 5.4M³/MIN	7BAR / 101.5PSI	ISUZU JE493ZYA	2100*980*1100	930	3 X 3/4"
CF275B-7	276CFM / 7.8M³/MIN	7BAR / 101.5PSI	ISUZU JE493ZLYA	2280*1224*1260	1100	2 X 3/4" + 1 X 1-1/4"
CF375B-7	375CFM / 10.6M³/MIN	7BAR / 101.5PSI	CUMMINS 4BTA3.9-C125	2657*1355*1466	1850	3 X 3/4" + 1 X 2"
CF400B-7	400CFM / 11.3M³/MIN	7BAR / 101.5PSI	CUMMINS 4BTA3.9-C125	2657*1355*1466	1850	3 X 3/4" + 1 X 2"
CF550B-7	550CFM / 15.5M³/MIN	7BAR / 101.5PSI	CUMMINS 6BTA5.9-C180	2970*1350*1465	1920	3 X 3/4" + 1 X 2"
CF750B-7	750CFM / 21.1M³/MIN	7BAR / 101.5PSI	DUMMINS 6CTA8.3-C260	3600*1750*1900	3600	1 X 3/4" + 1 X 2"
CF830B-7	830CFM / 23.4M³/MIN	7BAR / 101.5PSI	CUMMINS 6LTAA8.9-C360	3918*2200*2260	4200	1 X 3/4" + 1 X 2"
CF1800B-7	1800CFM / 50.7M³/MIN	7BAR / 101.5PSI	CUMMINS QSZ13-C550	3600*1950*1900	7155	1 X 3/4" + 1 X 2"
CF80B-10.5	80CFM / 2.3M³/MIN	10.5BAR / 152.25PSI	ISUZU JE493YA	1880*915*1230	830	2 X 3/4"
CF100B-10.5	100CFM / 2.8M³/MIN	10.5BAR / 152.25PSI	ISUZU JE493YA	1880*915*1230	830	2 X 3/4"
CF210B-10.5	210CFM / 5.9M³/MIN	10.5BAR / 152.25PSI	ISUZU JE493ZLYA	2280*1224*1260	1100	2 X 3/4" + 1 X 1-1/4"
CF390B-10.5	390CFM / 11M³/MIN	10.5BAR / 152.25PSI	CUMMINS 6BT5.9-C150	2970*1350*1465	1920	3 X 3/4" + 1 X 2"
CF460B-10.5	460CFM / 13M³/MIN	10.5BAR / 152.25PSI	CUMMINS 6BTA5.9-C180	2970*1350*1465	1920	3 X 3/4" + 1 X 2"
CF535B-10.5	535CFM / 15M³/MIN	10.5BAR / 152.25PSI	CUMMINS QSB5.9-C210	2970*1350*1465	1920	3 X 3/4" + 1 X 2"
CF655B-10.5	655CFM / 18.5M³/MIN	10.5BAR / 152.25PSI	CUMMINS 6CTA8.3-C260	3600*1750*1900	3600	1 X 3/4" + 1 X 2"
CF780B-10.5	780CFM / 22M³/MIN	10.5BAR / 152.25PSI	CUMMINS 6CTA8.3-C260	3600*1750*1900	3600	1 X 3/4" + 1 X 2"
CF830B-10.5	830CFM / 23.4M³/MIN	10.5BAR / 152.25PSI	CUMMINS 6LTAA8.9-C360	3600*1950*1900	4200	1 X 3/4" + 1 X 2"
CF1200B-10.5	1200CFM / 33.8M³/MIN	10.5BAR / 152.25PSI	CUMMINS QSZ13-C550	3918*2200*2260	7155	1 X 3/4" + 1 X 2"
CF1600B-10.5	1600CFM / 45M³/MIN	10.5BAR / 152.25PSI	CUMMINS QSZ13-C550	3918*2200*2260	7155	1 X 3/4" + 1 X 2"

● Please contact with CFAIR teams for more models of compressors.

● Specifications are subject to change without notice.

PNEUMATIC TOOLS

T SERIES

DETAILS

- Heat-treated forged body for excellent durability.
- Noise reduction muffler is optionally available.
- D-style handle for precise control

Model	Piston Diameter	Piston Stroke	Avg. Air Consumption	Weight	Impact Frequency	Air Pressure	Overall Length	Hose Size	Shank Size
TCA-7	35	120	35.3	7.2	20.8	6.3	465	19	26×80
TCD-20	42.85	60	39	10	33.3	6.3	520	19	26×80
TPB-40	44	146	56.8	18	17.5	6.3	660	19	25×108
TPB-60	57.15	100	66.7	30	23.3	6.3	345	19	32×152
TPB-90	66.67	152	36.7	42	25.3	6.3	723	19	32×152

M/B SERIES

Model	Bore (mm)	Stroke (mm)	Impact Rate (B.P.M)	Weight (kg)	Length (mm)	Air Consumption (CFM/m3/min)	Shank Size (mm)	Air Inlet (inch)
MO-2	32	163	1500	7.9	560	48.7 / 1.37	Ø24×72	3/4
MO-3	32	193	1320	8.2	595	1.43 / 50.8	Ø24×72	3/4
MO-4	32	228	1080	9	650	1.67 / 59.3	Ø24×72	3/4
B-1	38	198	960	14.1	665	2.74 / 97.4	Ø24×72	3/4
B-2	38	258	780	15.4	745	2.5 / 89	Ø24×72	3/4
B-3	38	293	720	16.2	795	2.5 / 89	Ø24×72	3/4

CHIPPING HAMMER & SPADE

Model	Diameter (mm)	Stroke (mm)	Air Pressure (Mpa)	Impact Energy J	Impact Frequency (HZ)	Air Consumption (L/S)	Pipe Joint Outer Diameter (mm)	Weight (kg)	Shank Size (mm)
C3	25	60	0.63	≥5	≥45	≤15	13	3.5	Ø17.5×60
C4	30	80	0.63	≥10	≥40	≤18	18	5.7	Ø17.5×60
C6A	30	105	0.63	≥14	≥32	≤21	18	6.7	Ø17.5×60
C6E	25	92	0.63	≥10	≥35	≤19	13	4.4	Ø17.5×60
Q6D	33	45	0.63	≥5	≥30	≤280	9	5.2	S18×60
Q8T	48	55	0.63	≥15	≥26	≤480	9	8	S18×60

G SERIES

Model	Bore (mm)	Stroke (mm)	Use air pressure (Mpa)	Weight (kg)	Length (mm)	Air consumption (L/S)	Shank Size (mm)	outer diameter
G10	38	155	0.63	10	570	≤26	Ø24×72	19
G12	38	155	0.63	11	570	≤26	Ø24×72	20
G15	38.5	155	0.63	11	570	≤26	Ø24×72	20
G16	40	155	0.63	13	345	≤26	Ø24×72	20
G20A	48	155	0.63	20	540	≤28	Ø30×87	20
G20B	40	155	0.63	14	600	≤26	Ø24×72	20
G25	48	155	0.63	42	723	≤28	Ø30×87	20
G30	48	155	0.63	20.5	600	≤28	Ø30×87	20

ROCK DRILLING

FUNCTIONAL USE

- Rock drills are used in mining, quarrying, tunnel construction, blasting, breaking rock, and drilling holes in construction and civil engineering projects.

ACCESSORIES

Model	Weight (kg)	Bore (mm)	Stroke (mm)	Impact Energy J	Impact Frequency (HZ)	Air consumption (L/S)	Air Hose (mm)	Water Hose (mm)	Shank (mm)
Y-18	18	60	50	32.7	30	25	19	13	22×108
Y-20	18	60	50	32.7	30	25	19	13	22×108
Y-24	24	70	70	62	31	56	19	13	22×108
Y-28	26	80	60	63	35	58	25	13	22×108

ACCESSORIES

Shovel Head	1#	2#	3#	4#	5#	6#	7#	8#
Length and Width	390×140	300×200	300×60	300×25	390×pointed	270×35	240×80	560×110
Weight (kg)	1.5	1.1	0.63	0.59	0.56	0.57	0.6	2

Our brand of goods packaging can accept the customer's customized packaging type, such as wooden box .

● For more pneumatic tool models, please contact CFAIR team.

ACCESSORIES, PRE-SALES AND AFTER-SALES SERVICES

ACCESSORIES SERVICE AND PACKAGING DELIVERY

ACCESSORIES SERVICE

CFAIR offers a comprehensive accessories service. When you purchase a machine, you can opt to have the corresponding maintenance accessories shipped with it, or you can buy them separately during maintenance.
Additionally, CFAIR provides air transportation services for your convenience.

PACKAGE CONDITION

CFAIR offers two superior packaging options to ensure your machine's safe transit: PE film with anti-collision cotton and wooden box packaging. These excellent packaging methods help prevent any damage or bumps during transportation.

DELIVERY TIME

CFAIR uses German technology to design oil-free screw air compressor heads to ensure safety and stability, ensure clean air output, reduce maintenance, extend service life, and be environmentally friendly.

PAYMENT METHOD AND AFTER-SALES SERVICE

TECHNICAL SERVICES

CFAIR offers advanced air compressor technology, ensuring seamless operation and intuitive controls, along with comprehensive after-sales support to meet all your maintenance and service needs efficiently.

TECHNICAL SERVICES

CFAIR calculates the warranty period after purchase and delivery (warranty period 1 year), and can be switched to a warranty plan (up to 1,000 operating hours) without any complex contract negotiations. Best of all: During the warranty period, there is no additional cost to pay, except for the standard maintenance costs.

WARRANTY PLAN

Our relentless efforts in supply chain management and quality control have earned CFAIR a strong market reputation, focusing on customer feedback to improve product reliability, durability, and delivery timeliness.

Our brand of goods packaging can accept the customer's customized packaging type, such as wooden box .

CFAIR ALL AIR COMPRESSOR SOLUTIONS

CFAIR COMPRESSED AIR MACHINE TYPE SPECTRUM

Small Air
- 50-535 CFM
- 101.5-152.25 PSI

(Pneumatic Pick for sale)

Medium Air
- 535-850 CFM
- 101.5-152.25 PSI

(Pneumatic Pick for sale)

Large Air
- 600-1800 CFM
- 152.25-435 PSI

(Pneumatic Pick for sale)

PORTABLE SCREW AIR COMPRESSOR
- 50-1800 CFM
- 101.5-435 PSI

EU/EPA PORTABLE SCREW AIR COMPRESSOR
- 50-1800 CFM
- 101.5-362.5 PSI

BOX-TYPE SCREW AIR COMPRESSOR
- 50-1800 CFM
- 101.5-435 PSI

AFTER-COOLER SCREW AIR COMPRESSOR
- 75-1600 CFM
- 101.5-362.5 PSI

HIGH PORTABLE SCREW AIR COMPRESSOR
- 75-1800 CFM
- 101.5-435 PSI

OIL-FREE SCREW AIR COMPRESSOR
- 150-1500 CFM
- 127.6-149.5 PSI

● Please contact with CFAIR teams for more models of compressors.